

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

Issued to: Fujian Lightning Optoelectronic Co Ltd
No.4,Yingbin Road,Optoelectric Industry Park,Hengshan
Village
Hutou Town,Anxi County
Quanzhou, Fujian Sheng 362000
China

**This is to certify that
representative samples of**

FPQU2 - Optical Isolators - Component
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 1577, 5th Ed, Issue Date: 2014-04-25, Revision Date: 2019-06-11

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
DIP6 , 4N25, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N26, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N27, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N28, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N29, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N30, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N31, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N32, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N33, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N35, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N36, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N37, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , 4N38, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , 6N135, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , 6N136, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , 6N137, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , 6N138, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , 6N139, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-0, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

DIP6 , CN17F-1, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-2, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-3, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-4, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-5, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-6, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-7, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-8, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CN17F-9, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-0, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-1, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-2, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-3, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-4, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-5, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-6, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-7, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-8, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , CNY17-9, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11AAX, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11AG1, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B0, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B1, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

DIP6 , H11B2, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B3, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B4, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B5, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B6, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B7, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B8, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11B9, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11BG2, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11DX, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G0, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G1, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G2, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G3, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G4, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G5, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G6, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G7, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G8, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11G9, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11L1, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11L2, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , H11L3, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac


Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

LSOP4/LSOP5 , TD1010, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1011, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1012, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1013, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1014, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1015, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1016, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1017, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1018, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1019, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1110, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1111, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1112, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1113, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1114, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1115, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1116, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1117, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1118, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TD1119, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD152, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD155E, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD155ER, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

SSOP4 , TD214, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 3750 Vac
SSOP4 , TD215, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 3750 Vac
SSOP4 , TD217, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 3750 Vac
DIP7/DIP8 , TD2530, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD2531, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD2600, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD2601, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD2611, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD2630, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD2631, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD2730, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD2731, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3010, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3010-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3011, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3011-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3012, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3012-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3021, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3021-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3022, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3022-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3023, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

DIP4 , TD3023-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3031, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3031-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3032, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3032-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3033, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3033-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3040-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3041, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3041-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3042, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3042-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3043, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3043-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3051, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3051-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3052, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3052-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3053, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3053-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3061, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3061-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3062, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

DIP4 , TD3062-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3063, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3063-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3071, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3071-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3072, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3072-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3073, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3073-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3081, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3081-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3082, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3082-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TD3083, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD3083-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD3120, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD3120L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD3120R, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD3150, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD3150L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD3150R, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD351, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD352, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

SOP4/SOP5 , TD354, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD3545, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD355, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD356, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD356L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD357, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD358, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TD359, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD4502, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD4503, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD4504, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD7840, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD810, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD814, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD8145, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD815, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD816, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD816L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD817, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD818, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD819, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD824, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD825, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

DIP7/DIP8 , TD826, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TD827, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD851, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TD852, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
TD852, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac, DIP4
DIP7/DIP8 , TD8D52, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL21L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3010, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3011, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3012, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL302, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3021, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3022, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3023, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3031, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3032, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3033, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3041, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3042, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3043, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3051, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3052, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3053, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

LSOP4/LSOP5 , TDL3061, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3062, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3063, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3071, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3072, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3073, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3081, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3082, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3083, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL314, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL340, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL341, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL343, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL345, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL346, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL347, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL349, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL351, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL352, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL354, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL3545, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL355, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL356L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

LSOP4/LSOP5 , TDL358, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL359, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL454, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL456, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL480, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL481, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL483, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL484, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL501, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL501(P), may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL501(W), may be followed by additional letters and/or numbers	Double protection optical isolators at 5000 Vac isolation voltage
LSOP6 , TDL50L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL601, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL601(P), may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL601(W), may be followed by additional letters and/or numbers	Double protection optical isolators at 5000 Vac isolation voltage
LSOP6 , TDL60L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL611, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL61L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDL701, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL701(P), may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP6 , TDL701(W), may be followed by additional letters and/or numbers	Double protection optical isolators at 5000 Vac isolation voltage
LSOP6 , TDL70L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR210, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

LSOP4/LSOP5 , TDLR211, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR212, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR213, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR214, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR215, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR216, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR217, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR218, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR219, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR410, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR411, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR412, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR413, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR414, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR415, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR416, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR417, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR418, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
LSOP4/LSOP5 , TDLR419, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3010, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3011, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3012, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3021, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

SOP4/SOP5 , TDM3022, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3023, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3031, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3032, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3033, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3041, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3042, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3043, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3051, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3052, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3053, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3061, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3062, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3063, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3071, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3072, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3073, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3081, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3082, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM3083, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM501, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM501R, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM601, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac


 Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

SOP4/SOP5 , TDM601R, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
SOP4/SOP5 , TDM701, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR0213, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR0223, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR1213, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR1223, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR210-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR210-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR210-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR211-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR211-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR211-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR212-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR212-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR212-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR213-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR213-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR213-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR214-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR214-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR214-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
TDR214-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac, DIP7/DIP8

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

DIP4 , TDR215-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR215-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR215-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR216-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR216-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR216-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR217-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR217-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR217-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR218-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR218-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR218-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR219-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR219-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR219-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR2213, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR2223, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR3213, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR3223, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR410-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR410-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR410-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR411-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

DIP6 , TDR411-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR411-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR412-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR412-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR412-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR413-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR413-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR413-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR414-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR414-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR414-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR415-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR415-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR415-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR416-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR416-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR416-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR417-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR417-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR417-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP4 , TDR418-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR418-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR418-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L501654-31-41109102-4
Report Reference E501654-20190114
Date 17-Jul-2023

DIP4 , TDR419-4L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP6 , TDR419-6L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac
DIP7/DIP8 , TDR419-8L, may be followed by additional letters and/or numbers	Double protection optical isolators, having an isolation rating up to 5000 Vac

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

